

Technical characteristics

Maximum speed (m/min - ft/min)	500 1640.4
Maximum web width (mm - in)	930 / 1330 / 1530 36.6 / 52.3 / 60.2
Maximum laminate width (mm - in)	915 / 1315 / 1515 36 / 51.7 / 59.6
Minimum laminate width (mm - in)	500 / 350 700 / 550 19.7 / 13.7 (with extensions) by 52.3 27.5 / 21.6 (with extensions) by 60.2
Maximum reel weight (kg - lb)	1000 / 1500 (upon request) 39.3 / 59.0 (upon request) 2204 / 3306 (upon request) 86 / 130 (upon request)
Maximum unwinder diameter (mm - in)	1000 / 1200 (upon request) 39.3 / 47.2 (upon request)
Minimum/maximum unwinder tension (N)	20 / 550 (700 upon request)

Technical characteristics

Maximum rewinder diameter (mm - in)	1000 / 1200 (upon request) 39.3 / 47.2 (upon request)
--	--

Minimum/maximum rewinder tension (N)	40 / 600 (750 upon request)
---	-----------------------------

Possibility of turret improvement	Yes
--------------------------------------	-----

Prodat	Premium/Excellence (upon request)
--------	-----------------------------------

Materials	LDPE, HDPE, LLDPE, BOPP, PET, PA, Alufoil, Paper, Films Coex
-----------	---

The technical characteristics are likely to change according to the chosen setup.